



30000 Hydraulic Oil HVI 46

Document version: November 1st 2018



Description

This hydraulic oil HVI 46 has been specially developed for heavy duty hydraulic systems of earth moving machinery and permanent installations that have to operate under high pressure and a wide temperature range. This oil is also very suitable for circulation lubrication (with the exception of turbines), for vacuum pumps and general machine lubrication. Important: This oil may not be used in systems in which silver-plated components are present.

According to the specifications of

AFNOR NF E 48-603 HV / NF E 48-690 / NF E 48-691
Cincinatti Milacron P-70
Denison HF-2
DIN 51524 part 3 HVLP
Eaton Vickers I-286-S / M-2950-S
ISO 11158 HV / 6743-4 HV

Packing units

ART. NO.	VOLUME	ITEMS PER UNIT	ITEMS PER PALLET
30001	1 L	6	450
30005	5 L	4	112
30020	20 L	1	30
30060	60 L	1	12
30205	205 L	1	2
30999	1000 L	1	-
P30000	bulk	1	-

Typical characteristics

TEST	VALUE	
Density at 15°C	0,875	kg/l
Kinematic viscosity at 40°C	46	mm ² /s
Kinematic viscosity at 100°C	8.1	mm ² /s
Viscosity index	150	
Flashpoint COC	218	°C
Pourpoint	-33	°C
Total Acid number	0.24	mgKOH/g